DRAWING LIST

DRAWING NUMBER: DRAWING CODE	DRAWING NUMBER: BALLOON NO	DESCRIPTION	QTY/ ASSY
060213MFA832		US-7 SYSTEMS TUNNEL ASSEMBLY	1
060213MFA833		US-7 SYSTEMS TUNNEL WELDMENT	1
060213MFA836		MOUNTING BLOCK	8

COMMERCIAL PARTS LIST

BALLOON NO	DESCRIPTION	QTY/ ASSY
C1	.375-24 UNJF-3A X 2.2 LONG, 100° FLATHEAD, SOCKET HEAD CAPSCREW, GRADE 8, ALLOY STEEL PER SAE J429, ZINC & YELLOW DICHROMATE PLATED FINISH.	16
C2	.375-24 UNC-2B HEX LOCKNUT, DISTORTED THREAD, GRADE 8, PLAIN STEEL, McMASTER-CARR# 90636A051 OR EQUIVALENT	16

TORQUE VALUES (USE LUBRICANT)

NO.	EFFECTIVE TORQUE
C2	28-30 FT-LBS.



SCALE 1/10

1. ALL FASTENERS ARE CLASSIFIED AS "FAIL-SAFE" FASTENERS AND WILL REQUIRE CERTIFICATION AND TESTING PER TABLE 1 IN NASA-STD-(I)-6008. CERTIFIED MATERIALS TEST REPORT (CMTR) REQUIRED.
2. HEX BOLTS AND HEX SOCKET HEAD CAP SCREWS SHALL CONFORM TO ANSI/ASTM B18.2.1.
3. HEX NUTS SHALL CONFORM TO ANSI/ASTM B18.2.2.
4. TORQUE VALUES SHOWN ARE EFFECITVE TORQUES ONLY. RUNNING TORQUE MUST BE MEASURED AND ADDED TO THE EFFECTIVE TORQUE VALUES TO DETERMINE THE TOTAL TORQUE. TIGHTEN FASTENERS TO WITHIN TOTAL TORQUE RANGE. USE LUBRICANT.
5. RECOAT THE ENTIRE ASSEMBLY WITH NATIONAL COATINGS RustShield A120 (BUFF) PRIMER FOLLOWING MANUFACTURERS SUGGESTED APPLICATION PROCEEDURE. THE COATING THICKNESS SHALL BE4-6 MILS (DRY) PER ASTM-D7091.
6. EXTERNAL SURFACES WITHIN INDICATED PAINT BOUNDARY: COAT WITH NATIONAL COATINGS AcryShield HIGH REFLECTIVE A590 (WHITE) TOPCOAT FOLLOWING MANUFACTURERS SUGGESTED APPLICATION PROCEDURE. THE COATING THICKNESS SHALL BE 6-10 MILS (DRY).
7. TOTAL COATING THICKNESS SHALL BE 10-16 MILS (DRY) AS MEASURED PER ASTM-D7091.
8. ESTIMATED WEIGHT: 80 LBS.







DATE/INITIAL	ECR	DEV	WAV	IMPLEMENTED

Released by AIX USS CMO on 2/22/08
For Procurement Use Only
DO NOT COPY

CHG	ZONE	DESCRIPTION	APP/DATE

REVISIONS

PRIOR TO USE VERIFY THE INTENDED PURPOSE IN PDM ("FOR" ATTRIBUTE)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

CONTRACT
CONTRACTOR
TASK ORDER

TOLERANCE ON	
.X	± -
.XX	± -
.XXX	± -
FRACTION	± -
ANGULAR	± -
BREAK EDGES	-

DRAFTER	DEZ/D. DRAGONY
ENGINEER	DER/A. HERRMAN
DESIGNER	DER/A. HERRMAN

DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994

????	SINGLE PART DRAWING
????-?	CHARTED PART DRAWING
C ?	COMMERCIAL PART
E ?	EXISTING PART

PDM REL LEVEL: Released PDM REVISION: -
PDM DATABASE:
MODEL NAME: 060213MFA832_US-7_SYS_TUN
CHECK FOR ANY OUTSTANDING ECO'S PRIOR TO USE

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
JOHN H. GLENN RESEARCH CENTER
LEWIS FIELD
CLEVELAND, OHIO

US-7 SEGMENT ASSEMBLY
060213MFA600

A832 US-7 SYSTEMS TUNNEL ASSEMBLY

SIZE	DRAWING NUMBER	REV	BLDG	AREA
E	060213MFA832	-	50	HI BAY

UNITS: INCH

SCALE:	INITIAL REL DATE	SHEET	DISCIPLINE
1/5 AND NOTED	02/21/2008	1 OF 1	MECHANICAL

PRO/E VERSION: Wildfire 2.0

SIZE E DRAWING NUMBER 060213MFA832 REV -

NAME:CMUSER CHECK:060213MFA832_SP4_FYA_TUN DATE:21-Feb-08 17:20:02